



SUPPLY CHAIN MANAGEMENT UNIT

ADVERTISEMENT

QUOTATION NO: 08/24/25

SUPPLY AND DELIVER RIDEON MOWER

Quotations are hereby called from suitably and experienced service providers to supply and deliver ride on mower as per the following specification:

Selling of quotation document will commence on **Tuesday, 13th of August 2024**. The **cut-off time for selling of quotation documents is 15h00 on Monday, 19th of August 2024**.

The physical address for payment is No.2 Nkonjane Road Sundumbili (cashiers office) Protection services, payment of a non-refundable fee of **R60.00** (inclusive of VAT)

ITEM	QTY	DESCRIPTION
1.	1	Ride on mower (Specification attached)

Quotations will be evaluated and adjudicated according to the following criteria:

The following PPPFA Regulations 2022 Specific Goals are applicable for 80/20 evaluation criteria:

Specific Goal	Maximum Allocated Points	Verification document
Enterprise Located within the Mandeni Municipality	7	CIPC registration documents
Enterprise 100% owned by Youth	6	ID Copy of directors and CSD
EME or QSE which is at least 100% owned by black people	5	ID Copy of directors and CSD
Enterprise 100% owned by Women	2	ID Copy of directors and CSD

- Supplier must be registered on the National Treasury's Central Supplier Database (CSD) and provide a proof of registration. The information recorded on your CSD report will be used to verify the following information: tax compliance status; company

Executive Committee

Cllr. TP Mdlalose (Mayor) | Cllr. BL Magwaza (Deputy Mayor) | Cllr. PM Sishi (Speaker) | Ex Officio Mr S Khuzwayo (Municipal Manager)
Cllr. SZ Mdlletshe | Cllr. ST Magwaza | Cllr. M. Shelembe | Cllr. MS Mdunge | Cllr. M. Mthembu

registration details; banking details; identity numbers of directors and employees in the service of the state

- Council's Supply Chain Management Policy.
- Quotation must be submitted on the official letterhead of your business and be valid for the period of 30 days. If quotations are called for number of items, unit price per item must be stated and total amount. No quotations will be considered from persons in the services of any organ of the state.
- Prices quoted must be firm and inclusive of VAT and unit price per item must be stated as well as total amount.
- Relevant required experience of **AT LEAST ONE** similar project. The Bidder is required to provide at least (one) award letter or purchase order.
- Company registration document with CIPC.
- Attach a full specification from the manufacturer, including brand and series of the machine you are quoting on.
- A certified copy of the most recent municipal account in which the business is registered. District municipality (water) and Local municipality (rates, electricity and other) or if the bidder is a tenant then a full lease agreement and a certificate from landlord indicating that the levies are not in arrears or a proof of residence and affidavit stating that the ward in which business is registered is exempted from paying rates, electricity and water. Failure to attach will lead to disqualification.
- All prospective tenderers will be screened in accordance with the National Treasury's Defaulters Database.
- Non-compliance with the above-mentioned criteria will lead to disqualification

Quotations are to be completed in accordance with the Specification and must be sealed in an envelope and marked "**SUPPLY AND DELIVER RIDE ON MOWER**" **QUOTATION NUMBER: 08/24/25** "and must be deposited in the Bid Box situated at the Reception: Civic Centre, 2 Kingfisher Road, Mandeni not later than **12h00, Tuesday, the 20th of August 2024**. **Late and verbal quotations will under no circumstances be considered.**

The Mandeni Municipality does not bind itself to accepting the lowest, or any tender, either wholly or in part or give any reason for such action.
Technical enquiries may be directed to Mrs. Londi Ngema and SCM enquiries to Lungisani Nduli (lungisanin@mandeni.gov.za) on 032-456 8200.


MR SG KHUZWAYO
MUNICIPAL MANAGER

Date: 13/08/2024

100 Series Lawn Tractor

Built in Greeneville, TN, the 100 Series is designed to make yard work simple. With affordable prices, comfortable designs, and a bumper-to-bumper warranty, it lets you focus on the real reason you have a lawn in the first place – to make memories.

- 17.5 hp (13 kW)* Engine
- 42-in. Edge™ Mower Deck
- Hydrostatic Transmission w/side-by-side pedals
- Spring-assisted hand grip lever raises and lowers deck easily
- Operator station is wide and comfortable
- 2 year/120 hour bumper-to-bumper warranty

Key Specifications:

- **Engine power:** 17.5 hp / 13 kW
- **Oil change:** No-tools oil drain with replaceable filter
- **Engine manufacturer/model:** 31R977 (M31)
- **Transaxle type:** TLT200 hydrostatic, two-wheel drive
- **Transaxle control:** Side-by-side pedals
- **Rear tires:** 20×8-8
- **Lift system type:** Spring-assisted hand-grip lever
- **Cutting width:** Edge™ mower deck, 42 inch / 107 cm

Warranty:

- 2 year/120 hour bumper-to-bumper* (*Term limited to years or hours used, whichever comes first, and varies by model.
- See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT.

Engine Specifications:

- **Power:** 17.5 hp / 13 kW
- **Displacement:** 30.5 cu in. / 500 cc
- **Manufacturer/model:** 31R977 (M31)
- **Type:** Overhead valve, full-pressure lube, oil filter
- **Cylinders:** One
- **Governor:** Mechanical
- **Choke/speed control:** Single lever with spring-return on choke
- **Cooling method:** Air
- **Air cleaner:** Cartridge
- **Oil change:** No-tools oil drain with replaceable filter

Fuel System:

- **Type:** Petrol
- **Fuel delivery:** Pulse pump and carburetor
- **Fuel gauge:** Mechanical, viewable from seat
- **Fuel tank location:** Rear
- **Fuel fill opening:** Center, 1.75 inch / 4.45 cm
- **Fuel tank capacity:** 2.4 U.S. gal. / 9.1 L
- **Electrical System:**
- **Battery:** 12 V / 300 CCA
- **Charging system:** Regulated, 8 amp
- **Engine starter:** Bendix type
- **Hour meter:** Yes

- **Headlights:** Two standard, incandescent
- **Taillights or reflector:** No
- **Backup lights:** No
- **Rear work lights:** No
- **12-V outlet:** No

Tranzaxle:

- **Type:** Hydrostatic, 2-wheel drive
- **Control:** Side-by-side pedals
- **Cruise control:** No
- **Oil cooler:** Fins and fan on transaxle
- **Oil filter:** Yes, not serviceable
- **Differential lock:** No
- **Forward speed:** 0-5.5 mph / 0-8.9 km/h
- **Reverse speed:** 0-3.2 mph / 0-5.2 km/h
- **Brakes:** Internal wet disk

Chassis:

- **Frame:** Full-length welded steel
- **Primer/paint:** E-coat/powder
- **Weight bracket:** Optional rear
- **Receiver hitch:** No
- **Front axle:** Cast-iron front axle, powdered-metal front wheel bushings
- **Spindle bushings:** No
- **Front tires:** 15×6-6
- **Rear tires:** 20×8-8
- **Hood material:** Molded-in color material reduces sound, will not rust or dent
- **Fender deck material:** Stamped steel
- **Floor mats:** Yes, with debris removing channels
- **Storage:** Storage tray with optional cover
- **Service interval decal:** Yes
- **Fender handles/grips:** No
- **Cup holder:** Yes
- **Equipment mounting:** CargO Mount™ system

Steering:

- **Type:** Sector and pinion with single drag link and tie rod
- **Four-wheel steer:** Not available on this model
- **Steering wheel:** Standard, diameter – 12 in. / 30.5 cm
- **Tilt steering wheel:** No
- **Turning radius:** 18 in. / 45.7 cm
- **Uncut circle radius:** 25 in. / 63.5 cm

Seat:

- **Type:** One piece
- **Seat back height:** 11 in. / 28 cm
- **Armrests:** No
- **Fore-aft adjustment:** While seated, 5.5 in. / 14 cm
- **Seat suspension:** Tilt, two coil springs

Lift System:

- **Type:** Spring-assisted hand-grip lever
- **Hydraulic outlets:** No
- **Mower cut height:** 13 positions, 1-4 in. / 2.5-10.2 cm

- **Cut height increments:** 0.25 in. / 0.64 cm
- **Preset cut height:** No

Mower Deck:

- **Type:** Side discharge
- **Cutting width:** Edge™ mower deck, 42 in. / 107 cm
- **Construction:** Stamped steel deck shell
- **Mower deck material:** Steel, 13 gauge / 0.09 in. / 2.3 mm
- **Mower wash port:** Yes
- **Mower drive system:** Manual power take-off (PTO)
- **Mower wheels:** Two
- **Mower wheel adjustment:** One bolt
- **Mower level adjustment:** Easy-level deck

Mower Attachability:

- **Type:** Slide under tractor
- **Front draft arms:** One spring clip
- **Rear draft arms:** Two spring clips
- **Mower wheels rotate:** No
- **Drive system:** Single belt

Safety:

- **Meets ANSI standard:** Yes
- **Meets OPEI standard:** Yes
- **Meets OPEI standard:** Yes
- **Backup protection:** Reverse Implement Option (RIO)
- **Safety video:** Yes

Optional Equipment:

- **Rear bagger:** 2-bag, 6.5 bu / 229 L
- **Mulching system:** Mulch cover or high-performance plug
- **Front blade:** 46 in. / 116.8 cm
- **Sprayer:** Tow-behind, 15 U.S. gal. / 56.8 L / Mounted, 15 U.S. gal. / Tow-behind only, 25 U.S. gal. / 94.6 L
- **Spreader:** Tow-behind only, 125-175 lb / 57.7-80 kg
- **Front bumper:** Styled front bumper
- **Weather protection:** Weather enclosure
- **Sun canopy:** Sun canopy
- **Bucket holder:** Yes, single bucket
- **Grass striping:** Lawn striping kit
- **Tow-behind tools:** 16

Dimensions:

- **Height:** 40 in. / 102 cm
- **Overall length:** 69.7 in. / 177 cm
- **Wheelbase:** 48.9 in. / 124.2 cm
- **Width with mower:** 55.2 in. / 140.2 cm
- **Width with mower (deflector raised for storage):** 46.5 in. / 118.1 cm
- **Weight:** Mower, no fuel, 414 lb / 188 kg

Features:

Powerful engine features full-pressure lubrication for long life

A 17.5-hp (13.0-kW), single-cylinder engine has plenty of power and torque to handle tough mowing, mulching, and bagging:

- Electronic ignition for fast starts
- Spring-return feature to ensure the operator will not mistakenly leave the throttle lever in the choke position
- Cast-iron cylinder liner for long engine life
- Overhead valves for excellent power and fuel economy
- Anti-vibration system
- Full-pressure lubrication and oil filter for cleaner oil, prolonging engine life, and extending the time between oil changes
 - More effective when operating the tractor on an incline
- Large fuel filter for trouble-free operation
- The capacity is 2.4 U.S. gal. (9.1 L).
- The fuel filler opening is conveniently located under the seat.

Frame made of full-length welded steel for reliability

The solid one-piece frame is constructed of 12-gauge, 0.105-in. (2.66-mm) steel

The front axle is constructed of solid cast iron that will not bend:

- Automotive-like steering system with sector and pinion steering gears and single drag link with a tie rod provides a very strong, low-effort, and tight-turning system.
- Three grease fittings, on both steering spindles and center pivot, allow for regular lubrication to help maintain easy steering and minimize wear.
- Large, 0.75-in. (1.9-cm) diameter wheel spindles provide excellent durability.

The front bumper is included on the S130, S140, S160, S170, and S180. It is available as an optional attachment for the S100, S110, and S120.